

Radial lead type

Discontinued

Series: HFZ Type : A




- Features Endurance :105°C 5000 h
Low impedance (1/3 to 1/4 of Series HF)


■ Specification

Operating Temp. Range	-55 to +105°C								
Rated W.V. Range	6.3 to 63 V .DC								
Nominal cap. Range	22 to 5600 μ F								
Capacitance	±20 % (120Hz/+20°C)								
DC leakage current	I < 0.01 CV (μ A) after 2min.								
tan δ	W.V.	6.3	10	16	25	35	50	63	(120Hz /+20°C) (max.)
	tan δ	0.17	0.15	0.10	0.08	0.07	0.06	0.05	
Add 0.02 per 1000μF for more than 1000μF items.									
Characteristics at Low Temp.	Impedance at -10°C, 100kHz <200 % of initial specified value at +20°C, 100kHz. (Impedance ratio at 100kHz.)								
Endurance	After 5000 hours with DC voltage and specified ripple current value applied at 105 ±2°C (the sum of DC and ripple peak voltage shall not exceed the rated working voltage), the capacitor shall meet the following limits.								
	Capacitance change	< ±20% of initial measured value							
	tan δ	< 200% of initial specified value							
	DC leakage current	< Initial specified value							
	Impedance	< 2 times of initial specified value							
Shelf life	After storage for 1000 hrs at +105±2°C with no voltage applied and then being stabilized at +20°C, capacitor shall meet the following limits.								
	Capacitance change	< ±15% of initial measured value							
	tan δ	< 150% of initial specified value							
	DC leakage current	< Initial specified value							
	Impedance	< 2 times of the initial specified value							

■ Explanation of Part Number



■ Dimensions in mm (not to scale)



Body Dia. φD	8	10	12.5	16	18
Body Length L	—	—	<25	>25	—
Lead Dia. φd	0.6	0.6	0.6	0.8	0.8
Lead space P	3.5	5.0	5.0	5.0	7.5

Design, Specifications are subject to change without notice. Ask factory for technical specifications before purchase and/or use. Whenever a doubt about safety arises from this product, please inform us immediately for technical consultation without fail.

Discontinued

■ Case size vs capacitance

Case size (φD x L)	W.V. (V.DC)	Capacitance (μF)						
		6.3	10	16	25	35	50	63
		8	13	20	32	44	63	79
8 × 15		330	220	150	82	56	33	22
8 × 20		470	390	220L	120L	82L	47	33L
10 × 16		390	330	220	120	82	39	33
10 × 20		560	470	330	180	120	68	47
10 × 25		820	680	390	220	150	82	56
10 × 30		1200L	1000L	560	330L	220L	120L	82L
12.5 × 20		1000	820	470	270	180	100	82
12.5 × 25		1200	1000	680	330	220	120	100
12.5 × 30		1500	1200L	820L	470L	330L	180L	120
12.5 × 35		2200L	1800L	1000L	560L	390L	220L	150L
12.5 × 40		2700L	2200L	1200L	680L	470L	270L	180L
16 × 20		1800	1200	820	470	330	180	150
16 × 25		2200	1800	1000	560	390	220	180
16 × 31.5		3300	2200	1500	820	560	330	220L
16 × 35.5		3900L	2700	1800L	1000L	680	390L	270
16 × 40		4700L	3300L	2200L	1200L	820L	470L	330L
18 × 20		2200S	1800S	1200	560S	470	220S	180S
18 × 25		2700	2200S	1500S	680	560S	270	220
18 × 31.5		3900	3300	1800	1000	820	390	330
18 × 35.5		4700	3900	2200	1200	1000	470	390
18 × 40		5600	4700	2700	1500	1200	560	470

L and S of above nominal capacitance are the last suffix code of part numbers.

ECA1AFZ102Lφ10 x 30

ECA1AFZ102φ12.5 x 25

■ Case size vs ripple current table

Case size (φD x L)	W.V. (V.DC)	Ripple Current (mA)rms at + 105°C, 100kHz		
		6.3 ~ 35	50	63
8 × 15		575	500	450
8 × 20		760	670	600
10 × 16		795	640	580
10 × 20		1015	890	820
10 × 25		1190	1040	950
10 × 30		1440	1300	1110
12.5 × 20		1400	1200	1140
12.5 × 25		1690	1440	1420
12.5 × 30		1950	1680	1620
12.5 × 35		2220	1850	1780
12.5 × 40		2390	2010	1950
16 × 20		1690	1470	1450
16 × 25		2010	1810	1750
16 × 31.5		2350	2120	2050
16 × 35.5		2550	2260	2220
16 × 40		2900	2410	2370
18 × 20		2010	1810	1750
18 × 25		2200	2000	1940
18 × 31.5		2800	2220	2110
18 × 35.5		2900	2460	2300
18 × 40		3000	2560	2510

■ Frequency correction factor for ripple current table

W.V.(V.DC)	Cap. (μF)	6.3 ~ 63			
		22 ~ 330	390 ~ 1000	1200 ~ 2200	2700 ~
Freq.(Hz)	60	0.55	0.70	0.75	0.80
	120	0.65	0.75	0.80	0.85
	1K	0.85	0.90	0.90	0.95
	10K	0.90	0.95	0.95	1.00
	100K	1.00	1.00	1.00	1.00

Design, Specifications are subject to change without notice. Ask factory for technical specifications before purchase and/or use. Whenever a doubt about safety arises from this product, please inform us immediately for technical consultation without fail.

Discontinued

■ Case size vs impedance table

Case size (φD x L)	W.V. (V.DC) S.V (V.DC)	Impedance(Ω)(+20°C)								
		6.3 ~ 35			50			63		
		100kHz	300kHz	500kHz	100kHz	300kHz	500kHz	100kHz	300kHz	500kHz
8 × 15		0.120	0.132	0.144	0.230	0.253	0.276	0.300	0.330	0.360
8 × 20		0.090	0.099	0.108	0.160	0.176	0.192	0.190	0.209	0.228
10 × 16		0.090	0.099	0.108	0.160	0.176	0.192	0.190	0.209	0.228
10 × 20		0.065	0.072	0.078	0.110	0.121	0.132	0.140	0.154	0.168
10 × 25		0.055	0.066	0.071	0.090	0.099	0.108	0.120	0.132	0.144
10 × 30		0.045	0.054	0.058	0.075	0.083	0.090	0.095	0.105	0.114
12.5 × 20		0.042	0.054	0.063	0.080	0.104	0.120	0.095	0.124	0.143
12.5 × 25		0.034	0.044	0.051	0.070	0.091	0.105	0.090	0.117	0.134
12.5 × 30		0.030	0.039	0.045	0.060	0.078	0.090	0.080	0.104	0.120
12.5 × 35		0.024	0.031	0.036	0.050	0.065	0.075	0.065	0.085	0.093
12.5 × 40		0.021	0.027	0.031	0.043	0.056	0.065	0.060	0.078	0.090
16 × 20		0.034	0.051	0.061	0.053	0.080	0.095	0.070	0.105	0.126
16 × 25		0.028	0.042	0.050	0.044	0.060	0.079	0.060	0.090	0.108
16 × 31.5		0.025	0.037	0.045	0.033	0.050	0.059	0.050	0.075	0.090
16 × 35.5		0.022	0.033	0.039	0.028	0.042	0.050	0.042	0.063	0.076
16 × 40		0.018	0.027	0.032	0.026	0.039	0.047	0.034	0.051	0.061
18 × 20		0.028	0.044	0.061	0.050	0.080	0.110	0.065	0.104	0.143
18 × 25		0.025	0.040	0.055	0.041	0.067	0.090	0.057	0.092	0.125
18 × 31.5		0.023	0.036	0.050	0.031	0.050	0.068	0.048	0.077	0.106
18 × 35.5		0.021	0.033	0.046	0.027	0.043	0.059	0.041	0.066	0.090
18 × 40		0.017	0.027	0.037	0.025	0.040	0.055	0.033	0.053	0.073

Design, Specifications are subject to change without notice. Ask factory for technical specifications before purchase and/or use. Whenever a doubt about safety arises from this product, please inform us immediately for technical consultation without fail.

⚠ Application Guidelines

1. Circuit Design

Ensure that operational and mounting conditions follow the specified conditions detailed in the catalog and specification sheets.

1.1 Operating Temperature and Frequency

Electrolytic capacitor electrical parameters are normally specified at 20°C temperature and 120Hz frequency. These parameters vary with changes in temperature and frequency. Circuit designers should take these changes into consideration.

(1) Effects of operating temperature on electrical parameters

- a) At higher temperatures, leakage current and capacitance increase while equivalent series resistance (ESR) decreases.
- b) At lower temperatures, leakage current and capacitance decrease while equivalent series resistance (ESR) increases.

(2) Effects of frequency on electrical parameters

- a) At higher frequencies, capacitance and impedance decrease while $\tan \delta$ increases.
- b) At lower frequencies, ripple current generated heat will rise due to an increase in equivalent series resistance (ESR).

1.2 Operating Temperature and Life Expectancy

(1) Expected life is affected by operating temperature. Generally, each 10°C reduction in temperature will double the expected life. Use capacitors at the lowest possible temperature below the maximum guaranteed temperature.

(2) If operating conditions exceed the maximum guaranteed limit, rapid electrical parameter deterioration will occur, and irreversible damage will result.

Check for maximum capacitor operating temperatures including ambient temperature, internal capacitor temperature rise caused by ripple current, and the effects of radiated heat from power transistors, IC's or resistors.

Avoid placing components which could conduct heat to the capacitor from the back side of the circuit board.

(3) The formula for calculating expected life at lower operating temperatures is as follows;

$$L_2 = L_1 \times 2^{\frac{T_1 - T_2}{10}} \quad \text{where,}$$

L1: Guaranteed life (h) at temperature, T1° C


L2: Expected life (h) at temperature, T2° C

T1: Maximum operating temperature (°C)


T2: Actual operating temperature, ambient temperature + temperature rise due to ripple current heating (°C)

A quick reference capacitor guide for estimating expected life is included for your reference.


■ Expected Life Estimate Quick Reference Guide



■ Failure rate curve



■ Typical failure modes and their factors



Design, Specifications are subject to change without notice. Ask factory for technical specifications before purchase and/or use. Whenever a doubt about safety arises from this product, please inform us immediately for technical consultation without fail.

1.3 Common Application Conditions to Avoid

The following misapplication load conditions will cause rapid deterioration to capacitor electrical parameters. In addition, rapid heating and gas generation within the capacitor can occur causing the pressure relief vent to operate and resultant leakage of electrolyte. Under extreme conditions, explosion and fire could result. Leaking electrolyte is combustible and electrically conductive.

(1) Reverse Voltage

DC capacitors have polarity. Verify correct polarity before insertion. For circuits with changing or uncertain polarity, use DC bipolar capacitors. DC bipolar capacitors are not suitable for use in AC circuits.

(2) Charge/Discharge Applications

Standard capacitors are not suitable for use in repeating charge/discharge applications. For charge/discharge applications consult us and advise actual conditions.

(3) Overvoltage

Do not apply voltages exceeding the maximum specified rated voltages. Voltage up to the surge voltage rating are acceptable for short periods of time. Ensure that the sum of the DC voltage and the superimposed AC ripple voltage does not exceed the rated voltage.

(4) Ripple Current

Do not apply ripple currents exceeding the maximum specified value. For high ripple current applications, use a capacitor designed for high ripple currents or contact us with your requirements.

Ensure that allowable ripple currents superimposed on low DC bias voltages do not cause reverse voltage conditions.

1.4 Using Two or More Capacitors in Series or Parallel

(1) Capacitors Connected in Parallel

The circuit resistance can closely approximate the series resistance of the capacitor causing an imbalance of ripple current loads within the capacitors. Careful design of wiring methods can minimize the possibility of excessive ripple currents applied to a capacitor.

(2) Capacitors Connected in Series

Normal DC leakage current differences among capacitors can cause voltage imbalances. The use of voltage divider shunt resistors with consideration to leakage currents, can prevent capacitor voltage imbalances.

1.5 Capacitor Mounting Considerations

(1) Double - Sided Circuit Boards

Avoid wiring Pattern runs which pass between the mounted capacitor and the circuit board. When dipping into a solder bath, excess solder may collect under the capacitor by capillary action and shortcircuit the anode and cathode terminals.

(2) Circuit Board Hole Positioning

The vinyl sleeve of the capacitor can be damaged if solder passes through a lead hole for subsequently processed parts. Special care when locating hole positions in proximity to capacitors is recommended.


(3) Circuit Board Hole Spacing

The circuit board holes spacing should match the capacitor lead wire spacing within the specified tolerances. Incorrect spacing can cause excessive lead wire stress during the insertion process. This may result in premature capacitor failure due to short or open circuit, increased leakage current, or electrolyte leakage.

(4) Land/Pad Pattern

The circuit board land/pad pattern size for chip capacitors is specified in the following table.

[Table of Board Land Size vs. Capacitor Size]



Size	a	b	c
A($\phi 3$)	0.6	2.2	1.5
B($\phi 4$)	1.0	2.5	1.6
C($\phi 5$)	1.5	2.8	1.6
D($\phi 6.3$)	1.8	3.2	1.6
E($\phi 8 \times 6.2L$)	2.2	4.0	1.6
F($\phi 8 \times 10.2L$)	3.1	4.0	2.0
G($\phi 10 \times 10.2L$)	4.6	4.1	2.0

Among others, when the size a is wide, back fillet can not be made, decreasing fitting strength.

※ Decide considering mounting condition, solderability and fitting strength, etc. based on the design standards of your company.

(5) Clearance for Case Mounted Pressure Relief Vents

Capacitors with case mounted pressure relief vents require sufficient clearance to allow for proper vent operation. The minimum clearances are dependent on capacitor diameters as follows.

- φ6.3 to φ16 mm : 2 mm minimum,
- φ18 to φ35 mm : 3 mm minimum.
- φ40 mm or greater: 5 mm minimum

(6) Clearance for Seal Mounted Pressure Relief Vents

A hole in the circuit board directly under the seal vent location is required to allow proper release of pressure.

(7) Wiring Near the Pressure Relief Vent

Avoid locating high voltage or high current wiring or circuit board paths above the pressure relief vent. Flammable, high temperature gas exceeding 100°C may be released which could dissolve the wire insulation and ignite.

(8) Circuit Board Patterns Under the Capacitor

Avoid circuit board runs under the capacitor as electrolyte leakage could cause an electrical short.

(9) Screw Terminal Capacitor Mounting

- Do not orient the capacitor with the screw terminal side of the capacitor facing downwards.
- Tighten the terminal and mounting bracket screws within the torque range specified in the specification.

1.6 Electrical Isolation of the Capacitor

Completely isolate the capacitor as follows.

- Between the cathode and the case (except for axially leaded B types) and between the anode terminal and other circuit paths.
- Between the extra mounting terminals (on T types) and the anode terminal, cathode terminal, and other circuit paths.

1.7 Capacitor Sleeve

The vinyl sleeve or laminate coating is intended for marking and identification purposes and is not meant to electrically insulate the capacitor.

The sleeving may split or crack if immersed into solvents such as toluene or xylene, and then exposed to high temperatures.

Always consider safety when designing equipment and circuits. Plan for worst case failure modes such as short circuits and open circuits which could occur during use.

- (1) Provide protection circuits and protection devices to allow safe failure modes.
- (2) Design redundant or secondary circuits where possible to assure continued operation in case of main circuit failure.

2. Capacitor Handling Techniques

2.1 Considerations Before Using

- (1) Capacitors have a finite life. Do not reuse or recycle capacitors from used equipment.
- (2) Transient recovery voltage may be generated in the capacitor due to dielectric absorption. If required, this voltage can be discharged with a resistor with a value of about 1 kΩ.
- (3) Capacitors stored for long periods of time may exhibit an increase in leakage current. This can be corrected by gradually applying rated voltage in series with a resistor of approximately 1 kΩ.
- (4) If capacitors are dropped, they can be damaged mechanically or electrically. Avoid using dropped capacitors.
- (5) Dented or crushed capacitors should not be used. The seal integrity can be compromised and loss of electrolyte/shortened life can result.

2.2 Capacitor Insertion

- (1) Verify the correct capacitance and rated voltage of the capacitor.
- (2) Verify the correct polarity of the capacitor before inserting.
- (3) Verify the correct hole spacing before insertion (land pattern size on chip type) to avoid stress on the terminals.
- (4) Ensure that the auto insertion equipment lead clinching operation does not stress the capacitor leads where they enter the seal of the capacitor. For chip type capacitors, excessive mounting pressure can cause high leakage current, short circuit, or disconnection.

2.3 Manual Soldering


- (1) Observe temperature and time soldering specifications or do not exceed temperatures of 350°C for 3 seconds or less.
- (2) If lead wires must be formed to meet terminal board hole spacing, avoid stress on the leadwire where it enters the capacitor seal.
- (3) If a soldered capacitor must be removed and reinserted, avoid excessive stress to the capacitor leads.
- (4) Avoid touching the tip of the soldering iron to the capacitor, to prevent melting of the vinyl sleeve.

2.4 Flow Soldering

- (1) Do not immerse the capacitor body into the solder bath as excessive internal pressure could result.
- (2) Observe proper soldering conditions (temperature, time, etc.). Do not exceed the specified limits.
- (3) Do not allow other parts or components to touch the capacitor during soldering.

2.5 Reflow Soldering for Chip Capacitors

- (1) For reflow, use a thermal conduction system such as infrared radiation (IR) or hot blast. Vapor heat transfer systems (VPS) are not recommended.
- (2) Observe proper soldering conditions (temperature, time, etc.). Do not exceed the specified limits.
- (3) Reflow should be performed one time. Consult us for additional reflow restrictions.



2.6 Other Soldering Considerations

Rapid temperature rises during the preheat operation and resin bonding operation can cause cracking of the capacitor vinyl sleeve. For heat curing, do not exceed 150°C for a maximum time of 2 minutes.

2.7 Capacitor Handling after Soldering

- (1) Avoid movement of the capacitor after soldering to prevent excessive stress on the leadwires where they enter the seal.
- (2) Do not use the capacitor as a handle when moving the circuit board assembly.
- (3) Avoid striking the capacitor after assembly to prevent failure due to excessive shock.

2.8 Circuit Board Cleaning

- (1) Circuit boards can be immersed or ultrasonically cleaned using suitable cleaning solvents for up to 5 minutes and up to 60°C maximum temperatures. The boards should be thoroughly rinsed and dried.

Recommended cleaning solvents include Pine Alpha ST-100S, Sunelec B-12, DK Beclear CW-5790, Aqua Cleaner 210SEP, Cold Cleaner P3-375, Telpen Cleaner EC-7R, Clean-thru 750H, Clean-thru 750L, Clean thru 710M, Techno Cleaner 219, Techno Care FRW-17, Techno Care FRW-1, Techno Care FRV-1, IPA (isopropyl alcohol)

* The use of ozone depleting cleaning agents are not recommended in the interest of protecting the environment.

- (2) Avoid using the following solvent groups unless specifically allowed for in the specification;

- Halogenated cleaning solvents: except for solvent resistant capacitor types, halogenated solvents can permeate the seal and cause internal capacitor corrosion and failure. For solvent resistant capacitors, carefully follow the temperature and time requirements of the specification. 1-1-1 trichloroethane should never be used on any aluminium electrolytic capacitor.
- Alkali solvents: could attack and dissolve the aluminum case.
- Petroleum based solvents: deterioration of the rubber seal could result.
- Xylene: deterioration of the rubber seal could result.
- Acetone: removal of the ink markings on the vinyl sleeve could result.

* Temperature measuring method: Measure temperature in assuming quantitative production, by sticking the thermo-couple to the capacitor upper part with epoxy adhesives.

Design, Specifications are subject to change without notice. Ask factory for technical specifications before purchase and/or use. Whenever a doubt about safety arises from this product, please inform us immediately for technical consultation without fail.

- (3) A thorough drying after cleaning is required to remove residual cleaning solvents which may be trapped between the capacitor and the circuit board. Avoid drying temperatures which exceed the maximum rated temperature of the capacitor.
- (4) Monitor the contamination levels of the cleaning solvents during use by electrical conductivity, pH, specific gravity, or water content. Chlorine levels can rise with contamination and adversely affect the performance of the capacitor.

* Please consult us for additional information about acceptable cleaning solvents or cleaning methods.

Type	Series	Cleaning permitted
Surface mount type	V(Except EB Series)	○
Lead type	Bi-polar SU	○
	M	○(~ 100V)
	KA	○
	Bi-polar KA	○
	FB	○
	FC	○
	GA	○
	NHG	○(~ 100V)
	EB	○(~ 100V)
TA	○	
Snap-in type	TS UP	○(~ 100V)
	TS HA	○(~ 100V)

2.9 Mounting Adhesives and Coating Agents

When using mounting adhesives or coating agents to control humidity, avoid using materials containing halogenated solvents. Also, avoid the use of chloroprene based polymers.

* After applying adhesives or coatings, dry thoroughly to prevent residual solvents from being trapped between the capacitor and the circuit board.

3. Precautions for using capacitors

3.1 Environmental Conditions

Capacitors should not be used in the following environments.

- (1) Temperature exposure above the maximum rated or below the minimum rated temperature of the capacitor.
- (2) Direct contact with water, salt water, or oil.
- (3) High humidity conditions where water could condense on the capacitor.
- (4) Exposure to toxic gases such as hydrogen sulfide, sulfuric acid, nitric acid, chlorine, or ammonia.
- (5) Exposure to ozone, radiation, or ultraviolet rays.
- (6) Vibration and shock conditions exceeding specified requirements.

3.2 Electrical Precautions

- (1) Avoid touching the terminals of the capacitor as possible electric shock could result. The exposed aluminium case is not insulated and could also cause electric shock if touched.
- (2) Avoid short circuiting the area between the capacitor terminals with conductive materials including liquids such as acids or alkaline solutions.

4. Emergency Procedures

- (1) If the pressure relief vent of the capacitor operates, immediately turn off the equipment and disconnect from the power source. This will minimize additional damage caused by the vaporizing electrolyte.
- (2) Avoid contact with the escaping electrolyte gas which can exceed 100°C temperatures. If electrolyte or gas enters the eye, immediately flush the eye with large amounts of water. If electrolyte or gas is ingested by mouth, gargle with water. If electrolyte contacts the skin, wash with soap and water.

5. Long Term Storage

Leakage current of a capacitor increases with long storage times. The aluminium oxide film deteriorates as a function of temperature and time. If used without reconditioning, an abnormally high current will be required to restore the oxide film. This current surge could cause the circuit or the capacitor to fail. Capacitor should be reconditioned by applying rated voltage in series with a 1000 Ω, current limiting resistor for a time period of 30 minutes.

5.1 Environmental Conditions (Storage)

Capacitors should not be stored in the following environments.

- (1) Temperature exposure above 35°C or below 15 °C.
- (2) Direct contact with water, salt water, or oil.
- (3) High humidity conditions where water could condense on the capacitor.
- (4) Exposure to toxic gases such as hydrogen sulfide, sulfuric acid, nitric acid, chlorine, or ammonia.
- (5) Exposure to ozone, radiation, or ultraviolet rays.
- (6) Vibration and shock conditions exceeding specified requirements.

6. Capacitor Disposal

When disposing of capacitors, use one of the following methods.

- Incinerate after crushing the capacitor or puncturing the can wall (to prevent explosion due to internal pressure rise). Capacitors should be incinerated at high temperatures to prevent the release of toxic gases such as chlorine from the polyvinyl chloride sleeve, etc.
- Dispose of as solid waste.
- Local laws may have specific disposal requirements which must be followed.

The application guidelines above are taken from:

Technical Report EIAJ RCR-2367 issued by the Japan Electronic Industry Association, Inc. -
Guideline of notabilia for aluminium electrolytic capacitors with non-solid electrolytic for use in electronic equipment.

Refer to this Technical Report for additional details.